

Key Features	
4 Stereo zone source component	Fixed or variable line output
IU rack chassis	1 Ethernet connection for all zones
Ethernet in	USB input
Uses standard network protocols	Universal voltage (100 ~ 240)
BluOS Features	
Supported File Formats	MP3, AAC, WMA, OGG Vorbis, WMA-L, FLAC, ALAC, WAV, AIFF, MQA, HRA
Supported Cloud Services	WIMP, Slacker Radio, Qobuz, HighResAudio, JUKE, Deezer, Murfie, HDTracks, Spotify, TIDAL, Napster, Microsoft Groove (with OneDrive), Classics Online, KKBox.
Supported Operating Systems	Microsoft Windows 7 SP1 or higher, Apple Macintosh OSX 10.7.5 or higher
Free Internet Radio	TuneIn Radio, iHeartRadio, Calm Radio, Radio Paradise
Integration Partners	Control 4, RTI, Crestron, URC, Lutron, PUSH, iPort, ELAN
Audio	
Rated Distortion	≤0.005%
Signal-to-Noise Ratio	110dB
Sample Rate	32 – 192kHz
Bit Depth	16 – 24
Connections Input	
Analogue	RCA Stereo
SPDIF	Optical (TOSLINK)
USB	Type A (for USB memory stick and supported peripherals – FAT 32 formatted) Type B (for computer audio interface)
+12V Trigger IN	12V ±20%
IR Input	3.5mm Jack
System Interrupt	For doorbell /alarms
Output	
Analogue	RCA Stereo x 4
SPDIF	Optical x 4 (TOSLINK) Coaxial x 4
+12V Trigger OUT	12V ±20%
Network	
Ethernet/LAN	Ethernet RJ45, GigE
General Specifications	
AC Power Supply	100-240V 50/60Hz
Standby Power	6W (Network Standby Mode)
Dimensions (W x H x D)	480 x 46 x 234mm (18 7/8 x 1 13/16 x 9 1/4")*
Net Weight	2.7kg (5.9lb)
Shipping Weight	3.8kg (8.4lb)